

Series 4, wall-mounted cooker hood, 90 cm, Stainless steel DWB97DM50B



DHZ1225	Chimney extension 1000 mm
DHZ1235	Chimney extension 1500 mm
DHZ9550	Brushed steel back panel
DHZ9551	Brushed steel back panel
DWZ0XX0J0	Long Life recirculation kit
DWZ1DX1B4	Clean Air Standard odor filter (repl.)
DWZ1DX1I4	Clean Air Standard recirculation kit
DWZ1DX1I6	Clean Air Plus recirculation kit
DWZ1FX5C6	Clean Air Plus recirc. kit external
DWZ1FX5D1	Long Life recirculation kit external
DZZ0XX0P0	Long Life odor filter (replacement)
DZZ1XX1B6	Clean Air Plus odor filter (replacement)

Box-design hood: performance and matching kitchen design bundled in one hood.

- **Silent:** maximal extractor performance with little noise
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **Metal Grease Filter:** cleans the air, captures grease, easy monthly clean-up.

Color chimney:	Stainless steel
Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the chimney:	583-912/583-1022 mm
Height of product, without chimney:	53 mm
Net weight:	14.0 kg
Type of control:	Electronic
Max. air extraction:	454 m³/h
Boost position output recirculating:	499 m³/h
Max. air recirculation:	404 m³/h
Boost position air extraction:	739 m³/h
Number of lights:	2
Noise level:	65 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
Odour filter:	No
Operating Mode:	Convertible
Optional accessories:	DHZ1225, DHZ1235, DHZ9550, DHZ9551, DWZ0XX0J0, DWZ1DX1B4, DWZ1DX1I4, DWZ1DX1I6, DWZ1FX5C6, DWZ1FX5D1, DZZ0XX0P0, DZZ1XX1B6
Type of lamps used:	LED
Grease filter type:	Kassette
Clean filter reminders:	No
Connection rating:	255 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation typology:	Wall-mounted
Material body:	Stainless steel
Plug type:	GB plug
Dimensions of the product, with chimney (if exists) (in):	x x
Dimensions of the packed product:	19.29 x 25.59 x 40.55
Net weight:	31.000 lbs
Gross weight:	42.000 lbs
Motor location:	Integrated motor in hood chimney
No-return airflow flap:	No
Length electrical supply cord:	130.0 cm
Dimensions of the product, with chimney (if exists):	635-1075 MM x 900.0 x 500.0 mm
Dimensions of the packed product (HxWxD):	... 490 x 650 x 1030 mm
Net weight:	14.0 kg
Gross weight:	19.2 kg



4 242005 053025

Series 4, wall-mounted cooker hood, 90 cm, Stainless steel DWB97DM50B

Box-design hood: performance and matching kitchen design bundled in one hood.

- DWB97DM50B
- DWB97DM50B

Variant:

Design:

- Appliance colour: stainless steel
- 90 cm Chimney hood
- Wall mounted hood
- Box brand design - stainless steel

Comfort:

- Suitable for ducted or re-circulated extraction
- For recirculated extraction or CleanAir recirculation kit (accessory) needed
- TouchControl for extractor speeds and light
- 3 speed + intensive operation via TouchControl
- Twin channel high performance fan motor
- Metal grease filter, dishwasher safe

Environment and safety:

- Energy Efficiency Class: B*
- Average Energy Consumption: 62.5 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Technical information:

- Power rating: 255 W
- Noise min./max. Normal Level: 52/65 dB*
- Ducted extraction rate according to DIN/EN 61591max. 453 m³/h
- Maximum extraction rate exhaust air 453 m³/h according to EN 61591
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 65 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
- Max. extraction rate: 739 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 324 m³/h
- Noise level in recirculation mode:
- Max. normal use: 74 dB(A) re 1 pW (61 dB(A) re 20 µPa sound pressure)
- 2 x 1,5W LED
- Light Intensity: 214 lux
- Colour Temperature: 3500 K

Measures:

- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm

- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 900 x 500mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with cleanAir module (HxWxD):
- 703 x 900 x 500mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 900 x 500mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney

* In accordance with the EU-Regulation No 65/2014

© 2010 Blackwell Publishing Ltd *Journal of Internal Medicine* 267: 103–111

