

# Built-in



	SICBN 3366 Premium	SICBN 3356 Premium
	<div style="display: flex; justify-content: space-around; font-size: 8px;"> <span style="background-color: #d9ead3; padding: 2px;">Bio Fresh</span> <span style="background-color: #d9ead3; padding: 2px;">No Frost</span> <span style="background-color: #d9ead3; padding: 2px;">Duo Cooling</span> <span style="background-color: #d9ead3; padding: 2px;">Ice Maker</span> <span style="background-color: #d9ead3; padding: 2px;">Soft System</span> <span style="background-color: #d9ead3; padding: 2px;">Soft Telescopic</span> </div>	<div style="display: flex; justify-content: space-around; font-size: 8px;"> <span style="background-color: #d9ead3; padding: 2px;">Bio Fresh</span> <span style="background-color: #d9ead3; padding: 2px;">No Frost</span> <span style="background-color: #d9ead3; padding: 2px;">Duo Cooling</span> <span style="background-color: #d9ead3; padding: 2px;">Soft System</span> <span style="background-color: #d9ead3; padding: 2px;">Soft Telescopic</span> </div>
Energy consumption (kWh/y)	340	335
Refrigerator capacity litre	179	179
BioFresh comp. litre	68	68
Freezer capacity litre	59	63
Number of shelves	4	4
Number of door racks	2	2
Number of freezer drawers	4 with LED lighting	3 with LED lighting
Number of BioFresh drawers	2 with LED lighting	2 with LED lighting
Electronic control	MagicEye with LCD temp. display, touch electronic	MagicEye with LCD temp. display, touch electronic
Refrigerator temperature range °C	+3°C to +9°C	+3°C to +9°C
Freezer temperature range °C	-14°C to -26°C	-14°C to -26°C
Temperature alarm	visual and acoustic	visual and acoustic
Defrost type	automatic	automatic
Interior light	LED light column on both sides	LED light column on both sides
Door alarm	acoustic	acoustic
IceMaker	fixed water connection 3/4"	
Ice cube output kg/24h	0.8	
SoftSystem	yes	yes
Door hinges	left, reversible	right, reversible
Product dimensions (H/W/D) cm	177+1.6/55.9/54.4	177+1.6/55.9/54.4
Cut out dimensions (H/W/D) cm	177.2-178.8/56-57/55	177.2-178.8/56-57/55
Net weight kg	79	76.6
Voltage V/Hz	220-240/50	220-240/50
<b>Installation Diagram</b>	<p>* Recommended: 560 mm</p>	<p>* Recommended: 560 mm</p>